




# Montage de la suspension Voiture

*Car Ceiling Light assembly instructions*



FABRICATION FRANCAISE / MADE IN FRANCE

LUMINAIRE DE CLASSE 2 - 230 VOLTS - 20 WATTS MAXIMUM - CONFORME A LA NORME EN-60598-1 ET EN-60598-2-1  
LUMINARY OF CLASS 2 - 230 VOLTS - 20 WATTS MAXIMUM - COMPLIANT TO THE STANDARD EN-60598-1 AND EN-60598-2-1



**Attention !**  
Merci de tenir hors de portée des enfants les petits éléments et le sachet plastique. Les articles en pièces détachées contiennent de petites pièces ou des angles aigus qui peuvent être dangereux pour les enfants. Il faut donc être prudent à l'ouverture du sachet et à l'assemblage du produit. Le montage de ce produit doit être effectué par un adulte.

**Be Careful !**  
This light and its content (plastic parts and plastic bags, small elements) needs to be kept away from children. Lights must always be installed by a qualified electrician

UNE QUESTION ? Contacgtez-nous au +33(0)6 52 35 83 55

NEED HELP ? Contact us at +33(0)6 52 35 83 55



Pour ce luminaire, nous vous recommandons une ampoule E27 de type LED (20W max)

For this light, we recommend an E27 bulb type LED (20W max)

Préparer les plis de la bande « capot-coffre » comme indiqué en A. Dévisser la bague de la douille.

*Start the assembly of the car by folding the piece as on picture A.Unscrew the ring of the socket.*

Assembler ensuite les 3 éléments (capot-coffre, les deux flancs, les vitre intérieures) en enfiler la douille dans le gros trou central B et C. Revisser la bague.

*Assemble the second part of the car body and the glass part then insert the socket through the hole in the central piece of the car as on pictures B and C. Screw the ring back to the socket.*

Clipser les quatre petites pattes vertes et les quatre petites pattes bleues (couleurs selon l'exemple de la notice) pour fermer la partie supérieure de la voiture. D,E,F

*Fix the 4 small clips around the car to keep the front and back side together with the side part and the glass part of the car, as on pictures D,E,F*

Avant de fermer le capot et le coffre, fixer la grande pièce percée d'un trou ovale sous la voiture.G

*Then place the oval piece at the back of the car and fix it with the 8 clips all around the car, as on picture G.*

Ensuite rabattre le coffre et le capot et clipser les pattes sous la voiture. H

*You can now close the car hood as on picture H, and insert the 2 clips to fix it.*

Fixer les phares I

*Place the car headlight as on picture I.*

Former les roues: Fermer la bande de roulement.J,K

Replier et clipser six pattes d'un coté sur le disque et 3 pattes de l'autre coté sur le demi-disque. L,M

The wheels : Close each strip on its top as on pictures J and K. Place a disk and use the 6 clips all around the strip to fix it to the strip, as on picture L. Place the half-disk on the other side of the wheel as on picture M.

Fixer ensuite les roues à la voiture. N

*Insert the wheels on the 3 slots, as on picture N.*